SANO handtrucks



# UNIKAR®

Manual lifting handtruck · Winch to 43–63” · Universal mount or forks



UNIVERSAL MOUNT WITH FORKS

## ITEMS INCLUDED WITH MACHINE

- Two-year manufacturer’s warranty

## FRAME AND CAPACITY

- Galvanized, chrome-plated steel frame for industrial and clean environments, with blue powder-coated cover
- Lifting capacity up to 330 lbs, depending on configuration

## DESIGN

- Tube construction for maximum strength at just 55 lbs
- Easy to use, highly maneuverable
- Low-noise winch with safety crank handle and a maintenance-free 1.97” lifting strap in place of chain or cable

## FEATURES

- Large rear wheels and swivel front casters roll over uneven surfaces and small steps
- Ergonomic handle with parking brake on both rear wheels

## OPTIONS

- Universal mount or forks
- Folding platform for the forks
- Attachable 23.6” × 23.6” toe plate

| ARTICLE NUMBERS BY LIFTING HEIGHT | UNIVERSAL MOUNT | WITH FORKS |
|---|---|---|
| 43” — standard height | 100 548 | 100 528 |
| 51” | 100 574 | 100 573 |
| 55” | 100 575 | 100 576 |
| 59” | 100 571 | 100 570 |
| 63” | 100 568 | 100 549 |

| TECHNICAL SPECIFICATIONS | |
|---|---|
| Max lifting capacity | 265 lbs at 11.8” center of gravity · 330 lbs at 8.3” |
| Total weight | 55 lbs, model dependent |
| Lifting height | 43” to 63”, model dependent |
| Width, caster to caster | 23” |
| Lifting speed | 2.75” per crank rotation, about 16 rotations for full lift |
| Rear wheels | 7.87” diameter, ball bearings |
| Front wheels | 1.97” double swivel casters |
| Shipping weight, excl. pallet | ≈ 62 lbs |
| Shipping dimensions | 38” × 32” × 60” |

| ACCESSORIES | |
|---|---|
| Stainless steel folding platform | 100 529 |
| Cargo support | 100 530 |
| Attachable toe plate, 23.6” × 23.6” | 053 124 |

TWO-YEAR WARRANTY

LIFT SMARTER. MOVE FASTER.

SANO Handtrucks LLC · 2330 Pro-Tec Way, Loganville, GA 30052 · 470-545-1792 · www.sanohandtrucks.com

Specifications subject to change without notice. © 2026 SANO Handtrucks LLC. All rights reserved.